Commercial waste, residual waste

Wastecode

W.RW.S-00004

Composition

- Combustible residual waste generated from manufacturing facilities or offices, stores and services.
- Size; fitting into garbage bags or containers of up to 240 liters.
- Nature and composition similar to household waste.

Other conditions

Caloric value 10-12 MJ/kg Total chlorine < 1 % Total Sulfur < 0,5 %

Waste in a compactor must be emptiable at an angle of 45 ° by gravitation.

Average nature and composition of wastes	Avg.	MinMax.
Paper/Cardboard	27 %	20-35 %
High calorific materials (including plastics)	28 %	25-40 %
Wood	12 %	5-15 %
Organic fraction (fruit, vegetables, garden)	13 %	5-15 %
Residue (total < 20 %)	Avg.	MinMax.
Metals	3 %	1-10 %
Textile, leather, rubber	6 %	1-10 %
Glass	4 %	1-10 %
Other (soil, debris, insulation material)	7 %	1-10 %

Incidental, max. 3% m/m:

Sand and soil, gypsum, debris, insulation material (glass wool, rock wool), styrofoam (EPS).

Excluded

- Commercial waste pressed into a roll-off container;
- (Li-ion) batteries;
- × Voluminous waste;
- Highly dusty substances; such
 as powders and sawdust: as powders and sawdust;
- × Electronic devices, kitchen appliances, other electronics;
- × (flammable) Liquids;
- Carpet and other flooring;

- Chemical waste;
 Aerosol cans, gas- and
- × PVC;
- Radioactive waste; such as
 Strong-smelling waste;
 Substances with 1 of th smoke detectors;
- × Solid rolls:
- × Fiber optic cables;
- Tires;Polishing cloths;
- × Bulky household waste and mattresses;
- × Firework;
- × (plant-based) Oils;

- nitrous oxide cylinders;
- × Substances with 1 of the following hazard labels:



Deviating waste materials or compositions must be requested separately. If it appears that the delivered batch does not meet these delivery requirements, PreZero reserves the right to adjust its processing.

